


Di-Clamp

Clamp Specifications

Model No.	Bolt Size	Clamping Force (tons)	Nut Torque* (ft./lbs)	Clamp Dimensions					
				F	G	H	J	K	L
DC-151	1"	15	250	1 7/16"	3 1/8"	2 1/4"	2 1/8"	1 5/8"	6"
DC-151B	1"	9	250	1 7/16"	3 1/8"	2 1/4"	2 1/8"	1 5/8"	6"
DC-201	3/4"	12	225	1 1/4"	3 1/8"	2 1/16"	2 1/8"	1 1/4"	5"
DC-201B	3/4"	7	225	1 1/4"	3 1/8"	2 1/16"	2 1/8"	1 1/4"	5"
DC-250H	5/8"	8	175	1 1/16"	2 3/8"	1 5/8"	1 5/8"	1"	4"
DC-250BH	5/8"	5	175	1 1/16"	2 3/8"	1 5/8"	1 5/8"	1"	4"


* +/- 10%

The DC-151 Series Clamp has a 1" DC-type T-slot head machined down to a 7/8" threaded bolt, complete with our patented DC clamp bar. **MODEL NO. KEY:** B = Heel block; H = Handle, may be added to all models to fit customer requirement. Dimension "L" can be up to 3" longer than stated. **NOTE:** Clamping force is reduced when using heel block.



Wardcraft can provide bolt lengths other than standard sizes. If overall dimension is greater than standard bolt length, please specify desired length when ordering.

To calculate bolt length:
 $L = H + B + \text{die shoe thickness} + 1"$



Ordering Information

When ordering or requesting a quote, please complete the following data.

Die shoe thickness: _____ Die weights: *top* _____ *bottom* _____

T-Slot Dimensions

Width of throat (A) _____ Depth of throat (B) _____ Width of head (C) _____ Depth of head (D) _____

Is die slotted: *yes* _____ *no* _____ Require heel block: *yes* _____ *no* _____ U-attachment needed: *yes* _____ *no* _____

NOTE: Please give depth of throat dimension "B" even if using standard T-slot.



Since 1897

WARDCRAFT
 Conveyors & Quick Die Change

ONE WARDCRAFT DRIVE ■ SPRING ARBOR ■ MICHIGAN 49283-9757 ■ tel 800-782-2779
 fax 517-750-2244 ■ www.quickdiechange.com or www.wardcraftconveyor.com